



# NTN Bearing de Mexico, S.A.



## 17 mm x 40 mm x 21 mm SKF NUTR 17 A Cam Follower and Track Roller - Yoke Type

Bearing No. NUTR 17 A

NUTR 17 A Bearing 2D drawings and 3D CAD models

Category	Cam Follower and Track Roller - Yoke Type
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.15
EAN	7316570840667
Product Group	B04144
Roller Surface Profile	Crowned
Profile	Yoke Type
Enclosure	Sealed
Rolling Element	Cylindrical Roller Bearing - Double Row
Relubricatable	Yes
Inch - Metric	Metric
Other Features	Full Complement   With Flanged Inner Ring   Labyrinth Seal
Long Description	17MM Bore; 40MM Roller Diameter; 20MM Roller Width; Crowned Roller; Yoke Type; Sealed; Cylindrical Roller Bearing - Double Row; Relubricatable
Category	Cam Followers Yoke Type
UNSPSC	31171530
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing



## NTN Bearing de Mexico, S.A.

Keyword String	Cam Follower
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	NUTR 17 A
Weight / LBS	0.331
Roller Diameter	1.575 Inch   40 Millimeter
d	0.669 Inch   17 Millimeter
Roller Width	0.787 Inch   20 Millimeter
roller diameter:	40 mm
radial static load capacity:	20 kN
roller width:	21 mm
roller material:	Chrome Steel
bore diameter:	17 mm
maximum rpm:	4500 RPM
roller shape:	Crowned
lubrication hole location:	Inner Ring
bearing element:	Cylindrical Rollers
axial dynamic load capacity:	19 kN
closure type:	Sealed
axial static load capacity:	22 kN
operating temperature range:	Maximum of +280 ° F
finish/coating:	Uncoated
radial dynamic load capacity:	14 kN
standards met:	ANSI/ABMA Standard 18.1
D	40 mm
d	17 mm
C	20 mm
B	21 mm
d <sub>1</sub>	22 mm
r <sub>1,2</sub> min.	1 mm
r, r <sub>3,4</sub> min.	0.5 mm
Basic dynamic load rating C	19 kN



## NTN Bearing de Mexico, S.A.

Basic static load rating $C_0$	22 kN
Fatigue load limit $P_u$	2.5 kN
Maximum dynamic radial loads $F_r$ max.	14 kN
Maximum static radial loads $F_{0r}$ max.	20 kN
Limiting speed	4500 r/min
Mass support roller	0.15 kg